

COMPONENT SELECTION GUIDE

GRADUATE

EXTRA LIGHT DOORS

RECOMMENDED TO WEIGHT: 120 KG HEIGHT: 2400 mm

DIRECTOR

LIGHT **DOORS**

RECOMMENDED TO WEIGHT: 200 KG HEIGHT: 3000 mm

MATADOR

DOORS

RECOMMENDED TO WEIGHT: 450 KG HEIGHT: 4500 mm

HERCULES

DOORS

RECOMMENDED TO WEIGHT: 650 KG HEIGHT: 6000 mm



GALVANIZED Custom Rolled to Length



EG2 34 x 30 1.00 mm



ED2 45 x 35 1.20 mm



EM1 61 x 50 1.50 mm



EH1 61 x 50 1.60 mm

2 WHEEL CARRIAGE

NYLON WHEELS Long Pins, Ball Bearing Race



EG7



ED7



EH7

NOT RECOMMENDED



NYLON WHEELS Long Pins, Ball or Needle Bearings



EG14LP



ED14LP



EH13LP



EH14LP

4 WHEEL CARRIAGE

STEEL WHEELS Long Pins, Needle Bearings



EG12



ED12LP



EH12LP



EH15ST Side Thrust

5 WHEEL TRACKMASTER

STEEL WHEELS Side Thrust Wheel for Wind Load







EH12ST Side Thrust



EH16ST Side Thrust

BOLT ON / WELD ON BRACKET



EG19



ED19



EH19



EH19

SINGLE SIDEFIX BRACKET

FLUSH MOUNT Use Combination of Bolt On Bracket & Sidefix Adaptor



EG19 EG23



ED19 ED120



EH19 EH120



EH19 EH120

SINGLE SIDEFIX BRACKET

STEPPED MOUNT For Typical Cladding Clearance



EG20



ED20C



EH20C



EH20C

SINGLE SUPPORT BRACKET

Use with EG19 / ED19 / EH19 Adjustable Single Track Support



EG23



ED23



EH23



EH23

DOUBLE SUPPORT BRACKET

Use with ED19 / EH19 Adjustable Double Track Support

NOT REQUIRED FOR THIS SERIES

DOUBLE SUPPORT



ED24



EH24



EH24

NYLON FLOOR GUIDE

For Above Ground Guides



EC FGP



EC FGP



EC FGP



EC FGP

DO IT YOURSELF SLIDING DOORS

FEATURES:

- · ON SITE FABRICATION · TEK SCREW ASSEMBLY
- · NO WELDING REQUIRED · REDUCED DAMAGE RISK
- · FAST ON SITE REPAIRS · GALVANIZED STEEL SECTION
- ECONOMICAL, MINIMUM WASTE • SIMPLE STRONG & LIGHTWEIGHT
- FULLY ENCLOSED CLADDING EDGES · SECTIONS CUSTOM ROLLED TO LENGTH

Now That's an Eltrak Advantage!

EF4 PERIMETER DOOR FRAMING







