

SPC V-Pulley (taper-lock)

Pulley (dw)	Grooves	Bush	d2 Max	Type	L	b	d3	d1	d	App. Kg
150	1	2012	50			25			159.6	0A
200	3	2517	60			85			209.6	10.41
	4	3020	75			110.5			209.6	11.57
	5	3535	90			136			209.6	14.38
	6	3535	90			161.5			209.6	16.13
	8	3535	90			212.5			209.6	16.93
212	3	3020	75			85			221.6	11.35
	4	3020	75			110.5			221.6	13.22
	5	3535	90			136			221.6	16.98
	6	3535	90			161.5			221.6	18.85
	8	3535	90			212.5			221.6	22.59
224	2	3020	75			59.5			233.6	10.97
	3	3020	75			85			233.6	12.97
	4	3535	90			110.5			233.6	17.72
	5	3535	90			136			233.6	19.71
	6	3535	90			161.5			233.6	21.71
	8	3535	90			212.5			233.6	25.69
236	3	3020	75			85			245.6	14.67
	4	3535	90			110.5			245.6	20.49
	5	3535	90			136			245.6	22.60
	6	3535	90			161.5			245.6	24.72
	8	3535	90			212.5			245.6	28.94
250	3	3020	75			85			259.6	16.76
	4	3535	90			110.5			259.6	23.91
	5	3535	90			136			259.6	26.16
	6	3535	90			161.5			259.6	28.42
	8	3535	90			212.5			259.6	32.93
265	3	3535	90			85			274.6	25.04
	4	3535	90			110.5			274.6	21.11
	5	3535	90			136			274.6	23.52
	6	3535	90			161.5			274.6	26.01
	8	3535	90			212.5			274.6	30.91
280	3	3535	90			85			289.6	19.55
	4	3535	90			110.5			289.6	22.23
	5	3535	90			136			289.6	24.91
	6	3535	90			161.5			289.6	27.60
	8	3535	90			212.5			289.6	32.84
300	3	3535	90			85			309.6	21.01
	4	3535	90			110.5			309.6	23.95
	5	3535	90			136			309.6	26.89
	6	3535	90			161.5			309.6	29.83
	8	4040	100			212.5			309.6	49.93
	10	4545	110			263.5			309.6	54.00
315	3	3535	90			85			324.6	22.04
	4	3535	90			110.5			324.6	25.18
	5	3535	90			136			324.6	28.32
	6	3535	90			161.5			324.6	31.45
	8	4040	100			212.5			324.6	44.28
	10	4545	110			263.5			324.5	60.00

SPC V-Pulley (taper-lock)



"Why compete against your supplier when you can be our partner"

Pulley (dw)	Grooves	Bush	d2 Max	Type	L	b	d3	d1	d	App. Kg
335	3	3535	90			85			344.6	22.60
	4	3535	90			110.5			344.6	27.60
	5	3535	90			136			344.6	31.11
	6	3535	90			161.5			344.6	34.62
	8	4040	100			212.5			344.6	47.97
	10	4545	110			263.5			344.6	81.00
355	3	3535	90			85			364.6	26.01
	4	3535	90			110.5			364.6	29.44
	5	3535	90			136			364.6	33.23
	6	3535	90			161.5			364.6	37.02
	8	4040	100			212.5			364.6	51.05
	10	4545	110			263.5			364.6	85.00
375	3	3535	90			85			384.6	25.10
	4	3535	90			110.5			384.6	30.72
	5	3535	90			136			384.6	35.84
	6	4040	100			161.5			384.6	46.39
	8	4545	110			212.5			384.6	59.70
	10	4545	110			263.5			384.6	92.00
400	3	3535	90			85			409.6	28.14
	4	3535	90			110.5			409.6	33.24
	5	3535	90			136			409.6	38.32
	6	4040	100			161.5			409.6	50.20
	8	4545	110			212.5			409.6	63.87
	10	5050	125			263.5			409.6	73.00
425	3	3535	90			85			434.6	28.75
	4	3535	90			110.5			434.6	33.76
	5	3535	90			136			434.6	45.51
	6	4040	100			161.5			434.6	56.22
	8	4545	110			212.5			434.6	64.97
	10	5050	125			263.5			434.6	105.00
450	3	3535	90			85			459.6	30.39
	4	3535	90			110.5			459.6	35.90
	5	4040	100			136			459.6	47.85
	6	4545	110			161.5			459.6	58.92
	8	5050	125			212.5			459.6	73.99
	10	5050	125			263.5			459.6	94.00
475	3	3535	90			85			484.6	32.46
	4	3535	90			110.5			484.6	38.41
	5	4040	100			136			484.6	50.60
	6	4545	110			161.5			484.6	61.46
	8	5050	125			212.5			484.6	77.64
	10	5050	125			263.5			484.6	125.00
500	3	3535	90			85			509.6	34.52
	4	3535	90			110.5			509.6	41.06
	5	4040	100			136			509.6	53.49
	6	4545	110			161.5			509.6	64.69
	8	5050	125			212.5			509.6	81.31
	10	5050	125			263.5			509.6	111.00

SPC V-Pulley (taper-lock)

Pulley (dw)	Grooves	Bush	d2 Max	Type	L	b	d3	d1	d	App. Kg
530	3	3535	90			85			539.6	36.82
	4	4040	100			110.5			539.6	50.27
	5	4040	100			136			539.6	62.18
	6	4545	110			161.5			539.6	73.77
	8	5050	125			212.5			539.6	85.60
	10	5050	125			263.5			539.6	145.00
560	3	3535	90			85			569.6	39.41
	4	4040	100			110.5			569.6	53.43
	5	4545	110			136			569.6	65.72
	6	5050	125			161.5			569.6	77.67
	8	5050	125			212.5			569.6	90.90
	10	5050	125			263.5			569.6	121.00
630	3	4040	100			85			639.6	52.10
	4	4545	110			110.5			639.6	66.03
	5	5050	125			136			639.6	79.30
	6	5050	125			161.5			639.6	87.39
	8	5050	125			212.5			639.6	102.88
	10	5050	125			263.5			639.6	130.00
800	3	4545	110			85			809.6	72.00
	4	5050	125			110.5			809.6	90.77
	5	5050	125			136			809.6	102.46
	6	5050	125			161.5			809.6	113.65
	8	5050	125			212.5			809.6	136.55
	10	5050	125			263.5			809.6	170.00
1000	4	5050	125			110.5			1009.6	117.11
	5	5050	125			136			1009.6	133.59
	6	5050	125			161.5			1009.6	149.80
	8	5050	125			212.5			1009.6	181.35
	10	5050	125			263.5			1009.6	230.00