











CG LARGE RUBBER WHEELS

250mm, 300mm & 400mm

Capacity: 100 - 600KG









Utility Wheel

- Puncture free for hand trolleys and wheelbarrows
- Comes with double sealed precision ball bearings for easy rolling

CODE		WHEEL DIAMETER (MM)	TYRE WIDTH	HUB LENGTH	SHAFT SIZE	WHEEL TYPE	BEARING TYPE	CAPACITY
								
PRP250		250	45	48	16MM (5/8")	BLACK RUBBER	PLAIN	100kg
R250/50C-PRYQPRECISION		250	50	60	5/8", 3/4", 1", 20m, 25mm	BLACK RUBBER	BALL	150kg
R300/50C-PRYQPRECISION		300	50	60	5/8", 3/4", 1", 20m, 25mm	BLACK RUBBER	BALL	150kg
R400/70C-PRYQPRECISION		400	70	80	5/8", 3/4", 1", 20m, 25mm	BLACK RUBBER	BALL	150kg
R250/75C-PRWQPRECISION		250	75	75	5/8", 3/4", 1", 20mm, 25mm	BLACK RUBBER	BALL	180KG

Solid Cushioned Wheel

- Puncture proof tyre where broken glass, nails, etc. may cause trouble.
- Use also on equipment where the tyre must not be flat, e.g. fire extinguisher trolleys, construction site equipment.

CODE		WHEEL DIAMETER (MM)	TYRE WIDTH	HUB LENGTH	SHAFT SIZE	WHEEL TYPE	BEARING TYPE	CAPACITY
								
R280/70R-SRBQPRECISION		280	70	60	5/8", 3/4", 1", 20mm, 25mm	BLACK RUBBER	BALL	220kg
R400X8-SQ10		400	95	80	1"	BLACK RUBBER	BALL	600kg

NOTE: R400X8-SQ10 can be ordered without the hub and bearings to fit directly onto a Holden HT hub (R400X8-SNB)