

# CG HI TEMP WHEELS ONLY

**CAPACITY: 70 - 400KG**

- Delrin wheels 265°C (Double ball bearing)
- Phenolic and glass filled wheels are used in bakery ovens, chillers or applications in which temperatures range from -30°C to +290°C
- Sealed precision maintenance free bearing
- Easy rolling, non-marking, tough Hi Temp Epoxy resin wheel
- 260° continuous exposure, 290° intermittent exposure










Phenolic



Glass Filled Nylon



Delrin

PART NO.	WHEEL DIAMETER (MM)	TYRE WIDTH	HUB LENGTH	SHAFT SIZE	WHEEL TYPE	BEARING TYPE	TEMP RATING	CAPACITY
								
MHH75	75	32	41	8MM , 12MM	GLASS FILLED NYLON	PLAIN	70KG = 150DEG	70KG
CGHTDNQ100	100	32	42	8MM	DELRIN	BALL	260DEG	115KG
MHH100	100	32	41	8MM , 12MM	GLASS FILLED NYLON	PLAIN	80KG = 150DEG	80KG
EE10040B	100	40	40	8MM	PHENOLIC	BALL	260DEG	150KG
EE10050B	100	50	60	½"	PHENOLIC	BALL	260DEG	250KG
EE12550B	125	50	60	½"	PHENOLIC	BALL	260DEG	300KG
EE15050B	150	50	60	½"	PHENOLIC	BALL	260DEG	400KG