

Low Height Heavy Duty Bolt Hole Series

CGLH BOLT HOLE

35mm, 40mm, 50mm, 75mm Nylon & Urethane

Capacity: 100KG - 600KG per castor










CGLHNNNA40BH
CGLHNNNA75BH

CGLHPUQ35BH



CGLHPUQ50BHTB

CGLHNNQ50BH M16 X 25
CGLHNNQ75BH M16 X 25

TYPE	CODE	WHEEL DIAMETER (MM)	TYRE WIDTH	WHEEL TYPE	BEARING TYPE	BOLT HOLE SIZE	CAPACITY	HEIGHT (MM)
								
Bolt Hole	CGLHPUQ35BH	35	25	Urethane	BALL	10	100kg	58
Bolt Hole Brake	CGLHPUQ35BHTB	35	25	Urethane	BALL	10	100kg	58
Bolt Hole	CGLHNNNA40BH	40 (twin)	22 x 2	Nylon	BALL	12	150kg	62
Bolt Hole	CGLHNNQ50BH M16 X 25	50	38	Nylon	BALL	M16 x 25 (Thread)	300kg	79
Bolt Hole Brake	CGLHNNQ50BHWB M16 X 25	50	38	Nylon	BALL	M16 x 25 (Thread)	300kg	79
Bolt Hole	CGLHPUQ50BH	50	33	Urethane	BALL	13	375kg	70
Bolt Hole Brake	CGLHPUQ50BHTB	50	33	Urethane	BALL	13	375kg	70
Bolt Hole	CGLHNNNA75BH	75 (twin)	22	Nylon	BALL	12	250kg	98
Bolt Hole	CGLHNNQ75BH M16 X 25	75	50	Nylon	BALL	M16 x 25 (Thread)	600kg	105
Bolt Hole Brake	CGLHNNQ75BHWB M16 X 25	75	50	Nylon	BALL	M16 x 25 (Thread)	600kg	105